

ELITE ROLLER GARAGE DOOR

LPCB SRI RATED



Certificate no. 931202
LPS1175 Issue 7

Secured by Design



Official Police Security Initiative

BASICS

APPLICATIONS	Medium to high security domestic or commercial garages.
FITTINGS	Internal face fit only.
SLAT	77mm aluminium double skinned slat with polyurethane foam insulation core.
Box	Roll-formed aluminium box with pressure-moulded aluminium alloy end plates.
GUIDES / BOTTOM SLAT	Extruded aluminium guide channels with brush inserts and extruded aluminium. Bottom slat with rubber weather seal.

FINISHES

SLAT BOX & GUIDES	White, cream white, ivory, beige, silver, grey, duck egg blue, chartwell green, sage green, fir green, moss green, velvet brown, brown, anthracite, black, painted golden oak or painted rosewood are all standard colours. Laminate wood effect and non-stocked RAL colours are subject to a 15% surcharge.
-------------------	--

WEIGHTS & MEASURES

WEIGHT PER M/2	5.5kg
MAX WIDTH	5,000mm
BOX SIZE	1650mm High = 250 X 250 - 2600mm = 300 X 300 - 4650mm = 400 X 400
MAX SURFACE AREA	20m/2
GUIDE WIDTHS	150mm to comply with LPCB certification. The guide cannels must be installed 30mm behind the opening, 180mm must be available each side of the opening for guides.

OPPERATION AND STANDARD FEATURES

ELECTRICS	Somfy or Elero motor with manual internal override crank handle and safety brake. Somfy or Teleco control panel with safety sensor, courtesy light and 2 key fobs.
-----------	--

WARRANTY

Comprehensive 5-year warranty covering parts, motor, controls and finish.



Only doors & shutters supplied by Aluroll and fitted in accordance with their installation regulations Qualify under Police Preferred Status. Pride Garage Doors follows all guidelines in relation to the installation of the ELITE Garage Door Range by Aluroll.